



TRI-BAND AXE11000 WI-FI 6E 10GE GATEWAY

CF60

The Gateway to **Hyperfibre**. Bring ludicrously fast Internet to home, business, and education.

DESIGNED TO GO FAST



The **10GE Wi-Fi 6E Gateway** is designed for 2000 Mbps, 4000 Mbps and 8000 Mbps Internet Plans. It comes with dedicated **10GE WAN** and **10GE LAN** ports.

WI-FI 6E IS HERE



Wi-Fi 6E is the future of Wi-Fi technology, providing better connectivity and a more seamless experience for users. With its extended frequency spectrum, **Wi-Fi 6E** provides **faster** and **more reliable** connectivity, even in Wi-Fi congested locations. This new technology also delivers lower latency, which makes it ideal for online gaming, video conferencing, and other real-time data intensive applications. **Wi-Fi 6E** enables higher data transfer speeds, which means you can download and stream high-quality content quickly without any buffering.

TURBOCHARGE YOUR WI-FI RANGE



The **10GE Wi-Fi 6E Gateway** comes equipped with the **6GHz Wi-Fi** band, as well as the **2.4GHz** and **5GHz Wi-Fi bands**. Each band includes a **4x4 antenna** setup for ultimate Wi-Fi coverage and throughput.

STAY IN TOUCH



The **10GE Wi-Fi 6E Gateway** includes **VoIP** functionality, allowing you to connect up to two telephones with **HD quality voice calls**.



TECHNICAL SPECIFICATIONS

DEVICE INTERFACES

- › 1 x 10GE WAN port
- › 1 x 10GE LAN port
- › 3 x 1GE LAN ports
- › 2 x Phone port (VoIP)
- › 1 x USB 3.0 port (storage only)
- › 1 x Reset button
- › 1 x WPS button
- › 1 x Wi-Fi on / off button
- › 1 x Power switch
- › 1 x Power jack
- › LED (Power / Internet / Wi-Fi / Phone)

ETHERNET WAN

- › PPPoE, DHCP client, Static IP

WIRELESS

- › Compatible with IEEE 802.11b, IEEE 802.11g, IEEE 802.11n, IEEE 802.11ac, IEEE 802.11ax
- › Supports concurrent tri-band Wi-Fi (2.4GHz/5GHz/6GHz) wireless
- › SSID broadcast or hidden
- › Auto / Manual channel selection
- › **Wireless security:** WPA2 / WPA2-PSK / WPA3

VOIP PROTOCOLS

- › SIP2.0
- › G.711, G.723 and G.726
- › FAX T.38 FAX Relay

NAS

- › File sharing function
- › DLNA support

SECURITY

- › Firewall
- › MAC filtering

ROUTING

- › Static Route
- › Dynamic Route (RIP v1/v2)
- › DMZ
- › Supports Layer 2 Bridge Mode

ADMINISTRATION

- › Quality of Service
- › SNMP
- › UPnP
- › Syslog
- › Web-based UI
- › Remote Login
- › TR-069 Auto provisioning
- › Backup / Restore Settings

ENVIRONMENTAL AND PHYSICAL

- › **Operating temperature:** 0–40°C
- › **Humidity:** 10%–95% non-condensing
- › **Storage temperature:** -10–60°C,
- › **Humidity:** 5%–95% non-condensing
- › DC Input Voltage 12V / 3.5A
- › **Dimensions:** 248 (W) x 200 (H) x 70 (D) mm
- › **Weight:** 1kg (approx.)

COMPLIANCE

- › RCM
- › NZ Telepermit



Trademarks and registered trademarks are the property of NetComm Wireless Pty Ltd or their respective owners. Specifications are subject to change without notice. Images shown may vary slightly from the actual product.



NETCOMM

HEAD OFFICE | SYDNEY
18-20 Orion Road
Lane Cove NSW 2066 Sydney
Australia | +61 2 9424 2070
www.netcomm.com



DZS

HEADQUARTERS | TEXAS
5700 Tennyson Pkwy
Suite 400 Plano, TX 75024
USA | +1 510 777 7000
www.dzsi.com



NetComm

NetComm Wireless Pty Ltd is a subsidiary of DZS Inc.